

Darest SHOP

D-Link DGS - 1008D



? Next possible delivery date: Jan 3, 2025

List Price:

~~CHF 87.05~~

Instant Savings:

-71%

CHF **25.70**

CHF **23.77** excl.

D-Link DGS 1008D - Switch - 8 x 10/100/1000 - desktop

Manufacturer

[D-Link](#)

EAN

790069252747

Manufacturer#

DGS-1008D/E

Description

8-port 10/100/1000M / auto-negotiation / half/full duplex / 1Gbps / MDI/MDI-X / auto-uplink / Desktop / Green Ethernet

Specification

Product Description	D-Link DGS 1008D - switch - 8 ports - unmanaged
---------------------	---

Device Type	Switch - 8 ports - unmanaged
-------------	------------------------------

Subtype	Gigabit Ethernet
---------	------------------

Ports	8 x 10/100/1000
-------	-----------------

Performance	Switching fabric bandwidth: 16 Gbps
-------------	-------------------------------------

MAC Address	4K entries
-------------	------------

Table Size	
Jumbo Frame Support	9000 bytes
Features	Flow control, auto-sensing per device, auto-negotiation, auto-uplink (auto MDI/MDI-X), store and forward, MAC address filtering, half duplex mode, full duplex mode, QoS, Cable Diagnostics Function, D-Link Green Technology
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x
Dimensions (WxDxH)	19.45 cm x 11.24 cm x 3.5 cm
Localisation	Continental Europe

Techn. Details

Device Type	Switch - 8 ports - unmanaged
Enclosure Type	Desktop
Subtype	Gigabit Ethernet
Ports	8 x 10/100/1000
Performance	Switching fabric bandwidth: 16 Gbps
MAC Address Table Size	4K entries
Jumbo Frame Support	9000 bytes
Features	Flow control, auto-sensing per device, auto-negotiation, auto-uplink (auto MDI/MDI-X), store and forward, MAC address filtering, half duplex mode, full duplex mode, QoS, Cable Diagnostics Function, D-Link Green Technology
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x
Status Indicators	Port transmission speed, power, link/activity
Interfaces	8 x 1000Base-T RJ-45
Power Device	External power adapter
Power Consumption	5.8 Watt

Operational	
MTBF	1,150,498 hours
Compliant Standards	FCC Class B certified, VCCI Class B ITE, cUL, ICES-003 Class B, C-Tick Class B, RoHS, LVD
Localisation	Continental Europe
Width	19.45 cm
Depth	11.24 cm
Height	3.5 cm
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)
Min Storage Temperature	-10 °C
Max Storage Temperature	70 °C
Humidity Range Storage	5 - 90% (non-condensing)

Related Prod.

Cat 6a Cables (6)

	Wirewin Slim Light - Patch cable - RJ-45 (M) to RJ-45 (M) - 2 m - U/FTP - CAT 6a - molded, round - white	CHF 10.85 CHF 10.04 excl.
		
	Wirewin Slim - Patch cable - RJ-45 (M) to RJ-45 (M) - 1.5 m - U/FTP - CAT 6a - molded, flat - grey	CHF 9.55 CHF 8.83 excl.
		
	Wirewin Slim - Patch cable - RJ-45 (M) to RJ-45 (M) - 25 cm - U/FTP - CAT 6a - molded, flat - red	CHF 6.35 CHF 5.87 excl.
		

Cat 6 Cables

	Wirewin Slim - Patch cable - RJ-45 (M) to RJ-45 (M) - 1 m - STP - CAT 6 - booted, flat - violet	CHF 8.45 CHF 7.82 excl.
		
	Wirewin Slim - Patch cable - RJ-45 (M) to RJ-45 (M) - 5	CHF 13.30



m - STP - CAT 6 - molded, snagless, flat - blue



CHF **12.30**

excl.



Wirewin Slim - Patch cable - RJ-45 (M) to RJ-45 (M) - 10

m - STP - CAT 6 - booted, flat - black



CHF **21.05**

CHF **19.47**

excl.

Date added: 2006-07-28 16:35:58 / SID: 288749 / DID: 64679